

14" Chop Saw Wheels - Type 1

- **A:** Aluminum Oxide - Metal & Steel.
- **WA: White Aluminum Oxide** -
Excellent on stainless steel, ferrous metals.
- **ZA: Zirconia Aluminum Oxide** - Metal & Stainless;
High performance cutting, recommended on thicker stock applications such as angle iron, angle bars.



Type 1

14" Double Reinforced - Angle Iron/Heavy Bars

- Zirconia grain, excellent on all ferrous metal applications, especially thicker stock
- Our #1 performing chop saw cut-off wheel.

UPC#	SIZE	SPEC.	RPM	CARTON QTY
36125	14 x 3/32 x 1	ZA24-S-BF	4,400	10

14" Double Reinforced - MR Stud

- Designed for drywall stud, aluminum shelving, thin metal

UPC#	SIZE	SPEC.	RPM	CARTON QTY
36124	14 x 3/32 x 1	A30-R-BF	4,400	10

14" Single Reinforced - Stainless

- Designed for stainless steel applications
- Contamination Free, Fe+S+Cl≤0.1%
- No iron, sulfur or chlorine



UPC#	SIZE	SPEC.	RPM	CARTON QTY
36123	14 x 3/32 x 1	WA36-P-BF	4,400	10

Application Chart - Chop Saw Wheels

SPEC.	Angle Iron - General Iron / Steel Bar	Metal Decking & Cable	Pipe Line	Wall Studs	High Tensile Steel	Stainless Steel Sheets	Stainless Steel Bars	Rail Cutting	Cast Steel	Gray Cast Iron	Ductile Iron Pipe & Concrete	Aluminum Alloys	Copper	Brass, Bronze	Titanium
A36P / A302P*	*	*	•	•	*	•	•	•	•	•	•				
A30R-Mr Stud				*											
A30N-ALU										•		*	•	•	•
WA36P					*	*	*								
ZA24S	*	*	*	*	*	*	*	*	•	•	•				

FERROUS METALS

CASTINGS

NON-FERROUS METALS

*A302 is single reinforced (SR). The SR blades have a lower G-ratio but higher cutting rate compared to the double reinforced.

* = Recommended

• = May Be Used