

# HIGH SPEED CUT-OFF WHEELS

HIGH SPEED CUT-OFF WHEELS

## 12"-16" High Speed Cut-Off Wheels - Type 1

- **A24R:** Aluminum Oxide - Metal & Steel, Stainless. General purpose. 14" are available in both double and triple reinforced.
- **A24T:** Aluminum Oxide - Metal Decking & Cable. Harder bond for more cuts on thinner metals. 14" are triple reinforced.
- **AC:** (Mix of A/C) - Used on Ductile Iron. 14" are available in both double and triple reinforced.
- **C16:** Silicon Carbide - Asphalt/Green Concrete
- **C24:** Silicon Carbide - Stone/Concrete



Type 1



- **EB – Electronically Balanced.** All 12-14" wheels are automatically balanced during manufacturing. All 12-14" wheels are guaranteed to be less than 3 and 3.5 grams out of balance. CGW wheels are safer, cause less vibration and are more consistent.



- CGW uses heavy duty fiberglass reinforcement, so our 12-14" high speed wheels meet speed specifications for all machines on the market.
- Premium 14" A24R, A24T, AC & 16" wheels are **triple reinforced (TR)** to provide extra safety.
- 12 & 14" wheels can be used with both gas and electric high speed machines.
- 12 & 14" wheels sold in (2) 10 piece retail packs and are master packed (contains 20 pieces).

### 12-16" A24-R, Metal, Steel, Stainless General Purpose

UPC#	SIZE	SPEC.	RPM	RETAIL PACK	MASTER PACK
<b>35587</b>	12 x 5/32 x 20mm	A24-R-BF	6,400	10	20
<b>35589</b>	12 x 5/32 x 1	A24-R-BF	6,400	10	20
<b>36158</b>	14 x 5/32 x 20mm	A24-R-BF	5,500	10	20
<b>36159</b>	14 x 5/32 x 1	A24-R-BF	5,500	10	20
<b>35599</b>	14 x 5/32 x 20mm	A24-R-BF <b>TR</b>	5,500	10	20
<b>35600</b>	14 x 5/32 x 1	A24-R-BF <b>TR</b>	5,500	10	20
<b>36142</b>	16 x 5/32 x 20mm	A24-R-BF <b>TR</b>	4,800	10	20
<b>36143</b>	16 x 5/32 x 1	A24-R-BF <b>TR</b>	4,800	10	20

### 12-14" A24-T, Metal Decking & Cable, Thinner Metals

UPC#	SIZE	SPEC.	RPM	RETAIL PACK	MASTER PACK
<b>36114</b>	12 x 5/32 x 20mm	A24-T-BF	6,400	10	20
<b>36115</b>	12 x 5/32 x 1	A24-T-BF	6,400	10	20
<b>36113</b>	14 x 5/32 x 20mm	A24-T-BF <b>TR</b>	5,500	10	20
<b>36126</b>	14 x 5/32 x 1	A24-T-BF <b>TR</b>	5,500	10	20

TR=Triple Reinforced