

12"-16" High Speed Cut-Off Wheels - Type 1

- **AC:** (Mix of A/C) - Used on Ductile Iron. 14" are available in both double and triple reinforced.
- **C16:** Silicon Carbide - Asphalt/Green Concrete
- **C24:** Silicon Carbide - Stone/Concrete



- **EB – Electronically Balanced.** All 12-14" wheels are automatically balanced during manufacturing. All 12-14" wheels are guaranteed to be less than 3 and 3.5 grams out of balance. CGW wheels are safer, cause less vibration and are more consistent.



- Premium 14" A24R, A24T, AC & 16" wheels are **triple reinforced (TR)** to provide extra safety.



Type 1

12-16" AC24-R, Ductile Iron

12-16" wheels for metal and masonry cutting applications.

UPC#	SIZE	SPEC.	RPM	RETAIL PACK	MASTER PACK
35590	12 x 5/32 x 20mm	AC24-R-BF	6,400	10	20
35592	12 x 5/32 x 1	AC24-R-BF	6,400	10	20
36160	14 x 5/32 x 20mm	AC24-R-BF	5,500	10	20
36161	14 x 5/32 x 1	AC24-R-BF	5,500	10	20
35601	14 x 5/32 x 20mm	AC24-R-BF TR	5,500	10	20
35602	14 x 5/32 x 1	AC24-R-BF TR	5,500	10	20
36144	16 x 5/32 x 20mm	AC24-R-BF TR	4,800	10	20
36145	16 x 5/32 x 1	AC24-R-BF TR	4,800	10	20

12-16" C24-R, Stone/Concrete

UPC#	SIZE	SPEC.	RPM	RETAIL PACK	MASTER PACK
35596	12 x 5/32 x 20mm	C24-R-BF	6,400	10	20
35598	12 x 5/32 x 1	C24-R-BF	6,400	10	20
35605	14 x 5/32 x 20mm	C24-R-BF	5,500	10	20
35606	14 x 5/32 x 1	C24-R-BF	5,500	10	20
36116	14 x 5/32 x 20mm	C24-R-BF TR	4,400	10	20
36117	14 x 5/32 x 1	C24-R-BF TR	4,400	10	20
36146	16 x 5/32 x 20mm	C24-R-BF TR	4,800	10	20
36147	16 x 5/32 x 1	C24-R-BF TR	4,800	10	20

12-14" C16-U, Asphalt/Green Concrete

UPC#	SIZE	SPEC.	RPM	RETAIL PACK	MASTER PACK
35593	12 x 5/32 x 20mm	C16-U-BF	6,400	10	20
35595	12 x 5/32 x 1	C16-U-BF	6,400	10	20
35603	14 x 5/32 x 20mm	C16-U-BF	5,500	10	20
35604	14 x 5/32 x 1	C16-U-BF	5,500	10	20