KNOT WIRE WHEEL BRUSHES

Knot Wire Wheel Brushe - Fast Cut

 Versatile in design, wire wheels brushes can be used horizontally or vertically.
(Correctly aligning brushes to work pieces allows wire tips to do the work.)

■ Knot Wire Wheel Brush - Standard

- Standard wire twist knot design for aggressive, yet uniform brushing action.
- For surface preparation, weld cleaning, heavy duty applications.
- For general cleaning, weld cleaning, removal of rubber flash, scale, rust, and pipeline cleaning.

■ Knot Wire Wheel Brush – Stringer Bead

- Tightly twisted wire knots easily reach into narrow or recessed areas for quick material removal.
- For pipeline welding junctions, cleaning bead welds.



Knot Wire Wheel Brush - Fast Cut

UPC#	SPEC	WIRE SIZE	ARBOR HOLE	MAX RPM	BOX QTY	MASTER PACK QTY	BULK UPC#	CATALOG PAGE#
Knot Wire Wheel Brush — Standard Twist								
60500	3" Radial Knot Carbon	.014	1/2-3/8	20,000	5	100		
60501	3" Radial Knot Stainless	.014	1/2-3/8	20,000	5	100		
60502	4" Radial Knot Carbon	.014	5/8-11	20,000	5	100	49635	142
60503	5" Radial Knot Carbon	.020	5/8-11	12,000	5	100		
60505	6" Radial Knot Carbon	.020	5/8-11	9,000	5	25		
Knot Wire Wheel Brush — Cable Twist								
60514	4" Cable Twist Carbon	.020	5/8-11	20,000	5	50	49637	142
60515	4" Cable Twist Stainless	.020	5/8-11	20,000	5	50	49638	142
Knot Wire Wheel Brush — Stringer Bead								
60520	4" Stringer Bead Carbon	.020	5/8-11	20,000	5	50	49639	142
60521	4" Stringer Bead Stainless	.020	5/8-11	20,000	5	50	49640	142
60522	5" Stringer Bead Carbon	.020	5/8-11	12,000	5	40		
60523	6" Stringer Bead Carbon	.020	5/8-11	12,000	5	25	49641	142
60524	6" Stringer Bead Stainless	.020	5/8-11	12,000	5	25		
60525	6-1/2" Stringer Bead Carbon	.020	5/8-11	12,000	5	25		
60526	6-1/2" Stringer Bead Stainless	.020	5/8-11	12,000	5	25		