

# SEMI-FLEX DISCS - RIGID



## Semi-Flex Discs - Rigid Strong, Phenolic Backing

- Rigid phenolic (fiberglass) backing for aggressive grinding applications.
- Phenolic backings are stronger than plastic and vulcanized fiber backings.
- Rigid disc design allows for more control when grinding corners and edges.
- Made for unlimited storage life. No deformation due to use, heat or humidity.
- Use wet or dry. **No back-up pad needed.**
- **Silicon Carbide discs for:** Concrete prep work - cleaning, grinding, sanding floors and walls. Floor coating removal - epoxy, glue, urethane, coatings, mastiks. Stone, brick and masonry. Non-ferrous metals. Fiberglass.
- **Aluminum Oxide discs for:** Metal fabrication, cast iron and foundry.



**SILICON CARBIDE**  
**ALUMINUM OXIDE**



Type 27  
Depressed Center

SEMI-FLEX DISCS

### 4-1/2" Diameter - Depressed Center 13,300 R.P.M.

UPC#	SIZE	SPEC.	CARTON QTY
49582	4-1/2 x 7/8	A-16-B	25
49584	4-1/2 x 7/8	A-24-B	25
49586	4-1/2 x 7/8	A-36-B	25
49583	4-1/2 x 5/8-11	A-16-B	10
49585	4-1/2 x 5/8-11	A-24-B	10
49587	4-1/2 x 5/8-11	A-36-B	10
49606	4-1/2 x 7/8	C-16-B	25
49608	4-1/2 x 7/8	C-24-B	25
49610	4-1/2 x 7/8	C-36-B	25
49607	4-1/2 x 5/8-11	C-16-B	10
49609	4-1/2 x 5/8-11	C-24-B	10
49611	4-1/2 x 5/8-11	C-36-B	10

### 7" Diameter - Depressed Center 8,600 R.P.M.

UPC#	SIZE	SPEC.	CARTON QTY
49594	7 x 7/8	A-16-B	25
49596	7 x 7/8	A-24-B	25
49598	7 x 7/8	A-36-B	25
49595	7 x 5/8-11	A-16-B	10
49597	7 x 5/8-11	A-24-B	10
49599	7 x 5/8-11	A-36-B	10
49618	7 x 7/8	C-16-B	25
49620	7 x 7/8	C-24-B	25
49622	7 x 7/8	C-36-B	25
49619	7 x 5/8-11	C-16-B	10
49621	7 x 5/8-11	C-24-B	10
49623	7 x 5/8-11	C-36-B	10

### 5" Diameter - Depressed Center 12,250 R.P.M.

UPC#	SIZE	SPEC.	CARTON QTY
49588	5 x 7/8	A-16-B	25
49590	5 x 7/8	A-24-B	25
49592	5 x 7/8	A-36-B	25
49589	5 x 5/8-11	A-16-B	10
49591	5 x 5/8-11	A-24-B	10
49593	5 x 5/8-11	A-36-B	10
49612	5 x 7/8	C-16-B	25
49614	5 x 7/8	C-24-B	25
49616	5 x 7/8	C-36-B	25
49613	5 x 5/8-11	C-16-B	10
49615	5 x 5/8-11	C-24-B	10
49617	5 x 5/8-11	C-36-B	10

