

Surface Conditioning Discs - Hook and Loop

- Impregnated with abrasive grain for fast material removal.
- Designed for long working life and resists loading.
- Use on steel, stainless steel, aluminum, titanium and alloys, fibre glass, plastic and glass fibre.
- *Use with 48224, 48225 and 48226 backup pad.



Surface Conditioning Discs with Arbor Hole

UPC#	SIZE	SPEC.	RPM	CARTON QTY
70029	4-1/2 x 7/8	Coarse – Gold	12,000	10
70030	4-1/2 x 7/8	Medium – Maroon	12,000	10
70031	4-1-2 x 7/8	Very Fine – Grey	12,000	10
70032	5 x 7/8	Coarse – Gold	10,000	10
70033	5 x 7/8	Medium – Maroon	10,000	10
70034	5 x 7/8	Very Fine – Grey	10,000	10
70035	7 x 7/8	Coarse – Gold	6,000	10
70036	7 x 7/8	Medium – Maroon	6,000	10
70037	7 x 7/8	Very Fine – Grey	6,000	10

Backing Pads

- 4-8" pads with internal 5/8-11 threads.
- 1/4" foam for medium stiffness and maximum grip for hook and loop discs.
- *Polypropylene back-up pad for right angle surface conditioning discs.



Hook & Loop Backing Pads

UPC#	SIZE	CARTON QTY
49532	4 x 5/8 -11	1
49533	4-1/2 x 5/8 -11	1
49534	5 x 5/8 -11	1
49535	6 x 5/8 -11	1
49536	7 x 5/8 -11	1
49537	8 x 5/8 -11	1

Right Angle Grinder Backing Pads

UPC#	SIZE	CARTON QTY
*48224	4-1/2 – polypropylene w/ 7/8" arbor hole	1
*48225	5 – polypropylene w/ 7/8" arbor hole	1
*48226	7 – polypropylene w/ 7/8" arbor hole	1