



900 Watt Beveling Tool KFM 9-3 RF

- Compact metal beveling tool for 45° chamfers and radii of 2 to 3 mm at visible edges
- Surfaces free from oxide and burrs as ideal preparation for the application of powder or paint coatings for maximum protection from corrosion
- One-touch controller: Patented, tool-free setting of the cutting depth in 0.1 steps; stop points for short setting times, and protection against unintentional adjustment of the cutting depth when working
- Slim cutter head with standard carbide indexable inserts and ball-bearing stationary seal ring for working in tubes and in curves
- Guide stop for a uniform finish and high quality of the surface when processing straight sheets
- Metabo Long-life motor with patented dust protection for long service life
- Thumbwheel controlled Vario-Constamatic (VC)-Full wave electronics ideal for working on materials requiring customised speeds, and at speeds which remain almost constant under load
- Electronic safety shutdown of the motor for safe working in case the tool stops unexpectedly
- Electronic overload protection, soft start and restart protection
- Slim design for ideal handling

Order no.	601751750
EAN code	4007430293428

No-load speed	4.500 - 11.500 rpm
Rated input power	900 W
Output power	470 W
Type of edges	Chamfer and radius
Max. chamfer width 45°	6 mm
Max. chamfer height at 45°	4 mm
Possible radii	R2 / R3
Grading of cutting depth setting	0,1 mm
Curves smallest internal Ø	13 mm
Weight (without power cable)	2,5 kg
Cable length	4 m

Scope of delivery

2 carbide indexable inserts 45° chamfer (ISO: DCMT 11 T 304), 2 Carbide indexable inserts radius R2, 2 Carbide indexable inserts radius R3, Guide Stop, Screwdriver Torx 15, Bow-type handle, MetaLoc case