



KNURLED RIVET NUTS

Metric Sizes

- Standard materials: steel, aluminum, and stainless steel.
- Standard plating: plain, zinc & cadmium.
- Low profile with a knurled body.
- Thin wall with a standard flange.

Metric Sizes							
Thread Size & Pitch	Grip Range	Under Head Length (Open End)	Under Head Length (Closed End)	Head Diameter	Head Thickness	Body Diameter	Hole Size
		+/- 0.38	+/- 0.38	Max	Nom	Max	+0.15
M4 x 0.7	0.50-2.00	10.67	18.80	9.91	0.76	6.73	6.75
M4 x 0.7	2.00-3.30	11.94	18.80	9.91	0.76	6.73	6.75
M5 X 0.8	0.50-3.30	12.07	25.15	10.54	0.76	7.52	7.60
M5 X 0.8	3.30-5.70	14.86	25.15	10.54	0.76	7.52	7.60
M6 X 1	0.70-4.20	14.73	30.23	12.70	0.76	9.91	10
M6 X 1	4.20-6.60	17.27	30.23	12.70	0.76	9.91	10
M8 X 1.25	0.70-3.80	17.53	35.31	17.40	0.89	13.46	13.50
M8 X 1.25	3.80-7.90	20.45	35.31	17.40	0.89	13.46	13.50
M10 X 1.50	0.70-3.80	17.53	35.31	17.40	0.89	13.46	13.50
M10 X 1.50	3.80-7.90	20.45	35.31	17.40	0.89	13.46	13.50
M12 X 1.75	1.60-5.10	29.21	49.78	21.97	1.19	17.40	17.47
M12 X 1.75	5.10-12.70	33.02	49.78	21.97	1.19	17.40	17.47

800-458-9353

www.hybrocosales.com