

NYLON LOCK NUTS

LIGHT HEX-FULL HEIGHT

- Standard materials: steel, and stainless steel.
- Steel nylon lock nuts are typically zinc plated.
- Recommended to be used with screws and bolts made of similar materials.

Size & Thread Diameter		Width Across Flats			Thickness		Side Height	Width Across
		Basic	Max	Min	Max	Min	Ref	Ref
2	0.0860	1/4	0.251	0.243	0.153	0.133	0.081	0.268
3	0.0990	1/4	0.251	0.243	0.153	0.133	0.081	0.268
4	0.1120	1/4	0.251	0.243	0.153	0.133	0.081	0.268
5	0.1250	1/4	0.251	0.243	0.153	0.133	0.081	0.268
6	0.1380	5/16	0.313	0.305	0.188	0.168	0.103	0.339
8	0.1640	11/32	0.345	0.336	0.239	0.219	0.140	0.374
10	0.1900	3/8	0.376	0.367	0.249	0.229	0.140	0.410
12	0.2160	7/16	0.439	0.430	0.328	0.298	0.225	0.482
1/4	0.2500	7/16	0.439	0.430	0.328	0.298	0.225	0.482
5/16	0.3125	1/2	0.502	0.492	0.359	0.329	0.250	0.552
3/8	0.3750	9/16	0.564	0.553	0.468	0.438	0.335	0.622
7/16	0.4375	5/8	0.627	0.616	0.468	0.438	0.324	0.698
1/2	0.5000	3/4	0.752	0.741	0.609	0.579	0.464	0.837
9/16	0.5625	7/8	0.877	0.865	0.656	0.626	0.469	0.978
5/8	0.6250	15/16	0.940	0.928	0.765	0.735	0.593	1.051
3/4	0.7500	1-1/8	1.064	1.052	0.890	0.860	0.742	1.191
7/8	0.8750	1-5/16	1.252	1.239	0.999	0.969	0.790	1.403
1	1.0000	1-1/2	1.440	1.427	1.078	1.016	0.825	1.615
1-1/8	1.1250	1-11/16	1.627	1.614	1.203	1.141	0.930	1.826
1-1/4	1.2500	1-7/8	1.815	1.801	1.422	1.360	1.125	2.038
1-1/2	1.5000	2-1/4	2.197	2.159	1.640	1.578	1.313	2.444

Michigan

400 N. Clinton St.
Stockbridge, MI 49285
Phone: 517-851-8757
Fax: 517-851-7722

Tennessee

3100 Ambrose Ave.
Nashville, TN 37207
Phone: 615-352-6701
Fax: 615-352-6722

Wisconsin

Milwaukee, WI 53220
Phone: 414-344-8034