

NYLON LOCK NUTS

HEAVY HEX-THIN HEIGHT

- Standard materials: steel, and stainless steel.
- Steel nylon lock nuts are typically zinc plated.
- Recommended to be used with screws and bolts made of similar materials.
- Approximately 35% less thick from top to bottom compared to NU series.

| Size & Thread Diameter | | Width Across Flats | | Thickness | | Side Height | Width Across Corners |
|---------------------------|--------|--------------------|-------|-----------|-------|-------------|----------------------|
| | | Max | Min | Max | Min | Ref | Ref |
| 1/4 | 0.2500 | 0.502 | 0.492 | 0.296 | 0.266 | 0.194 | 0.552 |
| 5/16 | 0.3125 | 0.564 | 0.553 | 0.328 | 0.298 | 0.212 | 0.622 |
| 3/8 | 0.3750 | 0.690 | 0.679 | 0.421 | 0.391 | 0.251 | 0.766 |
| 7/16 | 0.4375 | 0.752 | 0.741 | 0.453 | 0.423 | 0.316 | 0.837 |
| 1/2 | 0.5000 | 0.877 | 0.865 | 0.546 | 0.516 | 0.360 | 0.978 |
| 5/8 | 0.6250 | 1.064 | 1.052 | 0.624 | 0.594 | 0.428 | 1.191 |
| 3/4 | 0.7500 | 1.252 | 1.239 | 0.718 | 0.688 | 0.488 | 1.403 |
| 7/8 | 0.8750 | 1.440 | 1.427 | 0.796 | 0.766 | 0.535 | 1.615 |
| 1 | 1.0000 | 1.627 | 1.614 | 0.922 | 0.860 | 0.600 | 1.826 |

Michigan

400 N. Clinton St.
Stockbridge, MI 49285
Phone: 517-851-8757
Fax: 517-851-7722

Tennessee

3100 Ambrose Ave.
Nashville, TN 37207
Phone: 615-352-6701
Fax: 615-352-6722

Wisconsin

Milwaukee, WI 53220
Phone: 414-344-8034