



STRUCTURAL BLIND RIVETS

External Locking

- Standard materials: Aluminum, Steel, and Stainless .
- Dome and countersunk head styles available.

Material	Rivet Size	Grip Range	Head Style	Length	Head Diameter	Head Height	Mandrel Diameter
		Min- Max		Max	Max	Max	Nom
Aluminum	3/16"	0.062-0.250	Dome	0.416	0.400	0.090	0.118
		0.062-0.437	Dome	0.577			
	1/4"	0.080-0.375	Dome	0.556	0.530	0.117	0.157
		0.080-0.625	Dome	0.847			
		0.125-0.500	Countersunk	0.722	0.420	0.070	0.157
Steel	3/16"	0.062-0.250	Dome	0.297	0.400	0.090	0.118
		0.062-0.437	Dome	0.360			
	1/4"	0.080-0.375	Dome	0.422	0.530	0.117	0.157
		0.080-0.625	Dome	0.485			
		0.125-0.500	Countersunk	0.547	0.420	0.070	0.157
Stainless	3/16"	0.062-0.250	Dome	0.375	0.400	0.090	0.118
		0.062-0.437	Dome	0.437			
	1/4"	0.080-0.375	Dome	0.500	0.530	0.117	0.157
		0.080-0.625	Dome	1.195			
		0.125-0.500	Countersunk	1.320	0.420	0.070	0.157

800-458-9353

www.hybrocosales.com