

TOP LOCK NUT GRADE "C"

- Standard materials: steel & stainless steel.
- Steel nylon lock nuts are typically zinc plated.
- Recommended to be used with screws and bolts made of similar materials.

Size in Inches	Width Across Flats			Overall Thickness		Hex Height
	Nominal	Max	Min	Max	Min	Min
1/4	7/16	0.4385	0.428	0.226	0.212	0.145
5/16	1/2	0.5020	0.489	0.273	0.258	0.166
3/8	9/16	0.5645	0.551	0.337	0.320	0.198
7/16	11/16	0.6895	0.675	0.385	0.365	0.223
1/2	3/4	0.7520	0.736	0.448	0.427	0.262
9/16	7/8	0.8770	0.861	0.496	0.473	0.286
5/8	15/16	0.9395	0.922	0.559	0.535	0.329
3/4	1-1/8	1.1270	1.088	0.665	0.617	0.382
7/8	1-5/16	1.3145	1.2690	0.776	0.724	0.450
1	1-1/2	1.5020	1.4500	0.887	0.831	0.513

Michigan

400 N. Clinton St.
Stockbridge, MI 49285
Phone: 517-851-8757
Fax: 517-851-7722

Tennessee

3100 Ambrose Ave.
Nashville, TN 37207
Phone: 615-352-6701
Fax: 615-352-6722

Wisconsin

Milwaukee, WI 53220
Phone: 414-344-8034